


## 24-Hour Plus K14

PRODUCT	DIMENSIONS	K14	
	Seat depth from lumbar support	460-520 mm	
	Seat depth	470 mm	
	Seat width	510 mm	
	Backrest height from seat	590 mm	
	Backrest height from seat (with headrest)	710-810 mm	
	Backrest width	500 mm	
	Seat height	440-550 mm	
	Width between armrests	470-540 mm	
TECHNICAL DESCRIPTION			
Seat	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified.		
Backrest	Internal structure in multilayered beech wood anatomically shaped, 13 mm thickness. Low formaldehyde emission according to class E1. Wood FSC certified. PVC profile seal for impact protection.		
Headrest	<b>SL300:</b> height adjustable headrest (h 110 mm) without locks. Internal structure in wood, supporting structure in chromed steel (Ø 12 mm).		
Padding	Seat in PU-Flex, 75 mm thickness and 55 g/L density. Backrest in PU-Flex, 25-45 mm variable thickness and 45 g/L density. Lumbar area with double padding. Headrest in PU-Flex, 20 mm thickness and 55 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.		
Upholstery	<p><b>H24/250</b> Composition: 63% polyamide Cradura™, 14% virgin wool, 10% viscose Red. Lenzing FR™, 11% polyester, 3% metallic fibers Weight: 452 g/lmt Abrasion: ISO 12947-2 (&gt; 500.000 Martindale cycles) Pilling: ISO 12945-2 (4-5) Colour fastness to rubbing: ISO 105-X12 (Dry/Wet 4-5) Colour fastness to light: ISO 105-B02 Xenotest (Level 6-7) Flammability: UNI 9175 (Class 1), EN 1021-1+2 (M2), BS 5852-0+1, California TB 117 Colour: Black 024 / Grey 027 / Light blue 026 / Red 021 The fabric has a non-slip effect ideal for intensive use. The fabric is optimised to resist to velcro straps. Depending on the season, it gives the feeling of a pleasant warmth or freshness.</p> <p><b>MIRAGE</b> Composition: 100% polyester FR Weight: 460 g/lmt Abrasion: UNI EN ISO 12947 (&gt; 100.000 Martindale cycles) Colour fastness to light: UNI EN ISO 105-B02 Xenotest (Level 5-6) Flammability: IT - Class 1, EN 1021-1+2, DIN 4102 (B1), BS 5852 Crib 5, ÖNORM B3825 (B1), ÖNORM 3800-1 (Q1), FR - M1, NF D 60-013 (AM18), California TB 117 Colours: Black 724 / Dark grey 739 / Dark blue 734 / Red 721</p>		

Rev. 0	01-06-2017	24-Hour Plus: K14	Page 1 of 2
Rev 1	01-11-2019	24-Hour Plus: K14	Page 1 of 2

## 24-Hour Plus

### K14

Armrests	<b>0840C:</b> 4D armrests adjustable in height, width, depth and rotation. Supporting structure in polished aluminum with top in black soft polyurethane.
Lumbar support	Bidirectional Schukra mechanical system, lumbar support adjustable in height and depth by two knobs positioned on the back of the backrest.
Mechanism	<b>TP:</b> TENSION TOP, synchronized backrest inclination of 26° and seat of 14° lockable in 6 positions, antishock system and side tension adjustment control. Seat negative inclination of -3°. Seat depth adjustment, run 62,5 mm. Up-down system for backrest height adjustment, lockable in 7 positions. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.
Base	<b>0907C:</b> 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs, anti-slip tips. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Castors	<b>0360:</b> soft castors (Ø 60 mm) in black nylon with non-marking polyurethane ring, self-braking.
<b>TEST</b>	
BS 5459-2+A2	

Rev. 0	01-06-2017	24-Hour Plus: K14	Page 2 of 2
Rev. 1	01-11-2019	24-Hour Plus: K14	Page 2 of 2