


24-Hour Plus K22

| PRODUCT | DIMENSIONS | K22 | |
|---|---|---|--|
|  | Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height from seat (with headrest) Backrest height adjustment Backrest width Seat height Width between armrests | 450-510 mm 480 mm 510 mm 640-700 mm 800-860 mm 60 mm 500 mm 440-550 mm 470-540 mm | |
| TECHNICAL DESCRIPTION | | | |
| Seat | Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. | | |
| Backrest | Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. | | |
| Headrest | LX300: fixed headrest. Supporting structure in chromed steel (Ø 10 mm). | | |
| Padding | Seat in PU-Flex, 75 mm thickness and 55 g/L density. Backrest in PU-Flex, 45 mm thickness and 45 g/L density. Lumbar area with double padding. Headrest in PU-Flex, variable thickness and 55 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC. | | |
| Upholstery | H24/250 Composition: 63% polyamide Cradura™, 14% virgin wool, 10% viscose Red. Lenzing FR™, 11% polyester, 3% metallic fibers Weight: 452 g/lmt Abrasion: ISO 12947-2 (> 500.000 Martindale cycles) Pilling: ISO 12945-2 (4-5) Colour fastness to rubbing: ISO 105-X12 (Dry/Wet 4-5) Colour fastness to light: ISO 105-B02 Xenotest (Level 6-7) Flammability: UNI 9175 (Class 1), EN 1021-1+2 (M2), BS 5852-0+1, California TB 117 Colour: Black 024 / Grey 027 / Light blue 026 / Red 021 The fabric has a non-slip effect ideal for intensive use. The fabric is optimised to resist to velcro straps. Depending on the season, it gives the feeling of a pleasant warmth or freshness. | | |
| | MIRAGE Composition: 100% polyester FR Weight: 460 g/lmt Abrasion: UNI EN ISO 12947 (> 100.000 Martindale cycles) Colour fastness to light: UNI EN ISO 105-B02 Xenotest (Level 5-6) Flammability: IT - Class 1, EN 1021-1+2, DIN 4102 (B1), BS 5852 Crib 5, ÖNORM B3825 (B1), ÖNORM 3800-1 (Q1), FR - M1, NF D 60-013 (AM18), California TB 117 Colours: Black 724 / Dark grey 739 / Dark blue 734 / Red 721 | | |

| | | | |
|--------|------------|-------------------|-------------|
| Rev. 0 | 01-06-2017 | 24-Hour Plus: K22 | Page 1 of 2 |
| Rev. 1 | 01-11-2019 | 24-Hour Plus: K22 | Page 1 of 2 |

24-Hour Plus K22

| | |
|------------------------|---|
| Armrests | 0840C: 4D armrests adjustable in height, width, depth and rotation. Supporting structure in polished aluminum with top in black soft polyurethane. |
| Mechanism | TP: TENSION TOP, synchronized backrest inclination of 26° and seat of 14° lockable in 6 positions, antishock system and side tension adjustment control. Seat negative inclination of -3°. Seat depth adjustment, run 62,5 mm. Up-down system for backrest height adjustment, lockable in 7 positions. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. |
| Lift action | Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550. |
| Base | 0907C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs, anti-slip tips. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. |
| Castors | 0360: soft castors (Ø 60 mm) in black nylon with non-marking polyurethane ring, self-braking. |
| ACCESSORIES | |
| LX600 | Pump activated air depth adjustable lumbar support. |
| TEST | |
| UNI EN 1335-1+2+3 | |
| D. Lgs. 81/2008 type A | |

| | | | |
|--------|------------|-------------------|-------------|
| Rev. 0 | 01-06-2017 | 24-Hour Plus: K22 | Page 2 of 2 |
| Rev. 1 | 01-11-2019 | 24-Hour Plus: K22 | Page 2 of 2 |