



Education Lab E-WD1012F

PRODUCT		DIMENSIONS	E-WD1012F
		Seat depth from lumbar support	360 mm
		Seat depth	430 mm
		Seat width	430 mm
		Backrest height from seat	350-420 mm
		Backrest height adjustment	70 mm
		Backrest width	400 mm
		Seat height	430-560 mm
TECHNICAL DESCRIPTION			
Seat	Structure in solid beech wood anatomically shaped, 27 mm variable thickness, natural water based painted. Low formaldehyde emission according to class E1.		
Backrest	Structure in solid beech wood anatomically shaped, 22 mm variable thickness, natural water based painted. Low formaldehyde emission according to class E1.		
Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.		
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.		
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.		
Castors	0302: hard castors (Ø 50 mm) in black nylon, self-braking.		
ACCESSORIES			
M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.		
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.		
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.		

Education Lab E-WD1462HF / E-WD1472HF

PRODUCT	DIMENSIONS	E-WD1462HF	E-WD1472HF
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	360 mm 430 mm 430 mm 350-420 mm 70 mm 400 mm 510-710 mm	360 mm 430 mm 430 mm 350-420 mm 70 mm 400 mm 610-860 mm


TECHNICAL DESCRIPTION

Seat	Structure in solid beech wood anatomically shaped, 27 mm variable thickness, natural water based painted. Low formaldehyde emission according to class E1.
Backrest	Structure in solid beech wood anatomically shaped, 22 mm variable thickness, natural water based painted. Low formaldehyde emission according to class E1.
Mechanism	AS2: A-SYNCHRON BI-LEVER, independent backrest inclination of 9° positive and 16° negative, seat of 6° positive and 4° negative, lockable in all positions. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	0351: glides in black nylon (h 55 mm / Ø 50 mm).

ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.

Education Lab E-WG1810P

PRODUCT	DIMENSIONS	E-WG1810P	
	Seat depth from lumbar support	380 mm	
	Seat depth	390 mm	
	Seat width	390 mm	
	Backrest height from seat	340-410 mm	
	Backrest height adjustment	70 mm	
	Backrest width	430 mm	
	Seat height	400-530 mm	


TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	GS: GAS LIFT, seat height adjustable. Knob activated backrest height adjustment.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Castors	0302: hard castors (Ø 50 mm) in black nylon, self-braking.

ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.

Education Lab E-WG1813P

PRODUCT	DIMENSIONS	E-WG1813P	
	Seat depth from lumbar support	440 mm	
	Seat depth	390 mm	
	Seat width	390 mm	
	Backrest height from seat	140-380 mm	
	Backrest height adjustment	240 mm	
	Backrest width	430 mm	
	Seat height	420-550 mm	


TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	AS3: A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, seat of 5° positive and 3° negative, lockable in all positions. With combined activation of tilting mechanism and backrest inclination. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Castors	0302: hard castors (Ø 50 mm) in black nylon, self-braking.

ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.

Education Lab E-WG1814P

PRODUCT	DIMENSIONS	E-WG1814P	
	Seat depth from lumbar support	400 mm	
	Seat depth	390 mm	
	Seat width	390 mm	
	Backrest height from seat	290-350 mm	
	Backrest height adjustment	60 mm	
	Backrest width	430 mm	
	Seat height	420-550 mm	


TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	PCP: PERMANENT CONTACT PLUS , backrest inclination of 20° lockable in 4 positions, antishock system and tension adjustment control. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P : 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Castors	0302 : hard castors (Ø 50 mm) in black nylon, self-braking.

ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.
M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.

Education Lab E-WG1860HP / E-WG1870HP

PRODUCT	DIMENSIONS	E-WG1860HP	E-WG1870HP
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	380 mm 390 mm 390 mm 340-410 mm 70 mm 430 mm 480-680 mm	380 mm 390 mm 390 mm 340-410 mm 70 mm 430 mm 580-830 mm


TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	GS: GAS LIFT, seat height adjustable. Knob activated backrest height adjustment.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	0351: glides in black nylon (h 55 mm / Ø 50 mm).

ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.

Education Lab E-WG1863HP

PRODUCT	DIMENSIONS	E-WG1863HP	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	440 mm 390 mm 390 mm 140-380 mm 240 mm 430 mm 500-700 mm	


TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	AS3: A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, seat of 5° positive and 3° negative, lockable in all positions. With combined activation of tilting mechanism and backrest inclination. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	0351: glides in black nylon (h 55 mm / Ø 50 mm).

ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.

Education Lab E-WG1864HP

PRODUCT	DIMENSIONS	E-WG1864HP	
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	400 mm 390 mm 390 mm 290-350 mm 60 mm 430 mm 500-700 mm	


TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods (Ø 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	PCP: PERMANENT CONTACT PLUS , backrest inclination of 20° lockable in 4 positions, antishock system and tension adjustment control. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P : 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	0351 : glides in black nylon (h 55 mm / Ø 50 mm).


ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.

Education Lab E-VL1514F

PRODUCT		DIMENSIONS	E-VL1514F
		Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	410 mm 420 mm 430 mm 300-370 mm 70 mm 390 mm 420-550 mm
TECHNICAL DESCRIPTION			
Seat	Structure in multilayered beech wood anatomically shaped, 10 mm thickness, natural water based painted. Low formaldehyde emission according to class E1.		
Backrest	Structure in multilayered beech wood anatomically shaped, 11 mm thickness, natural water based painted. Low formaldehyde emission according to class E1.		
Mechanism	PCP: PERMANENT CONTACT PLUS, backrest inclination of 20° lockable in 4 positions, antishock system and tension adjustment control. Push button activated backrest height adjustment. According to UNI EN 1335-3.		
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), black finish. Class 4 according to DIN 4550.		
Base	0902P: 5-star base (∅ 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.		
Castors	0302: hard castors (∅ 50 mm) in black nylon, self-braking.		
ACCESSORIES			
M-0311	Soft castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.		
M-0351	Glides in black nylon (h 55 mm / ∅ 50 mm). Instead of castors.		
0902C	5-star base (∅ 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.		

Education Lab E-VL1564HF / E-VL1574HF

PRODUCT	DIMENSIONS	E-VL1564HF	E-VL1574HF
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	410 mm 420 mm 430 mm 300-370 mm 70 mm 390 mm 500-700 mm	410 mm 420 mm 430 mm 300-370 mm 70 mm 390 mm 600-850 mm

TECHNICAL DESCRIPTION

Seat	Structure in multilayered beech wood anatomically shaped, 10 mm thickness, natural water based painted. Low formaldehyde emission according to class E1.
Backrest	Structure in multilayered beech wood anatomically shaped, 11 mm thickness, natural water based painted. Low formaldehyde emission according to class E1.
Mechanism	PCP: PERMANENT CONTACT PLUS, backrest inclination of 20° lockable in 4 positions, antishock system and tension adjustment control. Push button activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (∅ 28 mm) protected by steel tube (∅ 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (∅ 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	0351: glides in black nylon (h 55 mm / ∅ 50 mm).

ACCESSORIES

M-0311	Soft castors (∅ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (∅ 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (∅ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0902C	5-star base (∅ 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.