


Stainless Steel F-SS146HRF

PRODUCT		DIMENSIONS	F-SS146HRF
		Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height with castors Seat height with glides (optional)	440 mm 400 mm 340-380 mm 280-460 mm 180 mm 320 mm 520-620 mm 470-570 mm
TECHNICAL DESCRIPTION			
Seat	Structure in stainless steel AISI 304 18/10, 6 mm thickness. AISI 316 weld joints. Micro shot-peening finish treatment.		
Backrest	Structure in stainless steel AISI 304 18/10, 3 mm thickness. AISI 316 weld joints. Micro shot-peening finish treatment.		
Mechanism	FX: FIXED STRUCTURE , seat height lockable in 5 positions. Knob activated backrest height adjustment.		
Base	5-star base (Ø 600 mm) in stainless steel AISI 304 18/10. Micro shot-peening finish treatment.		
Castors	Castors (Ø 70 mm) in black nylon. Castor structure in stainless steel AISI 304 18/10, overall height 90 mm.		
ACCESSORIES			
M-0359S	Fixed glides in stainless steel AISI 304 18/10 (h 40 mm / Ø 30 mm), instead of castors.		

Rev. 1	01-01-2020	Stainless Steel: F-SS146HRF	Page 1 of 1
Rev. 0	01-06-2017	Stainless Steel: F-SS146HRF	Page 1 of 1