


## Stainless Steel F-SS147RF

PRODUCT		DIMENSIONS	F-SS147HRF
		Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height with castors Seat height with glides (optional)	440 mm 400 mm 340-380 mm 280-460 mm 180 mm 320 mm 620-810 mm 570-760 mm
TECHNICAL DESCRIPTION			
Seat	Structure in stainless steel AISI 304 18/10, 6 mm thickness. AISI 316 weld joints. Micro shot-peening finish treatment.		
Backrest	Structure in stainless steel AISI 304 18/10, 3 mm thickness. AISI 316 weld joints. Micro shot-peening finish treatment.		
Mechanism	<b>FX: FIXED STRUCTURE</b> , seat height lockable in 4 positions. Knob activated backrest height adjustment.		
Footrest	Fixed footrest (width 320 mm / radius 160 mm) in stainless steel AISI 304 18/10. Height from the ground 220 mm.		
Base	5-star base (∅ 600 mm) in stainless steel AISI 304 18/10. Micro shot-peening finish treatment.		
Castors	Castors (∅ 70 mm) in black nylon. Castor structure in stainless steel AISI 304 18/10, overall height 90 mm.		
ACCESSORIES			
M-0359S	Fixed glides in stainless steel AISI 304 18/10 (h 40 mm / ∅ 30 mm), instead of castors.		